

# Half-Pitch Dual-in-line Switches for SMT

## Specifications:

Contact rating:	24 V DC, 25 mA
Contact resistance:	< 50 mΩ
Insulation resistance:	100 MΩ at 500 V DC
Dielectric strength:	300 V AC for of 1 minute
Operating temperature:	-40 °C to +105 °C
Mechanical life:	2000 operations per pole
Contacts/Terminals:	copper alloy, gold-plated over nickel
Material:	case: PPS, UL 94 V-0, black slide: PA46, UL 94 V-0, white
Mounting:	on pc-board – SMD – 1.27 mm
Construction:	case sealed, slide recessed, sealed with protective tape
Slide position:	OFF

7

<b>Models:</b>	Poles	Length (A)			
DHS 104 N	4	6.12 mm			
DHS 106 N	6	8.66 mm			
DHS 108 N	8	11.20 mm			
DHS 110 N	10	13.74 mm			

Packing: on tapes

Models	Tape	Reel	Tape width (A)	Rapport (R)
DHS 104 N	2000 pieces	∅ 330 mm	16.0 mm	12.0 mm
DHS 106 N	2000 pieces	∅ 330 mm	16.0 mm	12.0 mm
DHS 108 N	2000 pieces	∅ 330 mm	24.0 mm	12.0 mm
DHS 110 N	2000 pieces	∅ 330 mm	24.0 mm	12.0 mm

