



## **Specifications:**

Contact rating:	50 V DC, 100 mA
Contact resistance:	< 50 mΩ
Insulation resistance:	> 1000 MΩ at 100 V DC
Capacity:	maximum 5 pF between 2 poles
Dielectric strength:	500 V, 50 Hz for the duration of 1 minute
Operating temperature:	–40 °C to +105 °C
Mechanical life:	minimum 1 000 operations per pole
Shock resistance:	contact interruption < 10 $\mu$ sec with triple shock in all 6 directions
	shock conditions: 20 G, 11 msec duration (sine half wave)
Vibration:	contact interruption: < 10 $\mu$ sec at vibration test in accordance with
	MIL-STD-202 D, method 204, condition C
Contacts:	copper beryllium, gold-plated over nickel
Terminals:	nickel silver, gold-plated
Material:	case: PPS, slided: PA
Construction:	case sealed, slide recessed, sealed with protective tape
Mounting:	on pc-board – SMD
Slide position:	OFF
Soldering conditions:	reflow-soldering

Models:

Series SMS 500							
Туре	Poles	Length (A)					
SMS 502	2	6.30 mm					
SMS 504	4	11.40 mm					
SMS 506	6	16.50 mm					
SMS 508	8	21.55 mm					
SMS 510	10	26.65 mm					





Packing:

## sticks or tapes

for order on tape: additional to type number: T example of order: SMS 502 T

			example of order: SMS 502 T				в
Models	Stick	Таре	Reel	Tape width (A)	Rapport (R)	<u>ø1.5</u>	<u>4.0</u> 2.0 0 0 0 0
	72 pieces; L 507 mm	2000 pieces		16.0 mm	8.0 mm	A.	
	40 pieces; L 507 mm 28 pieces; L 507 mm	1000 pieces 1000 pieces			12.0 mm 12.0 mm		
	20 pieces; L 507 mm	1000 pieces			12.0 mm	R	
SMS 510	16 pieces; L 507 mm	1000 pieces	Ø 330 mm	44.0 mm	12.0 mm		

washable

**•** 

00

SMS 502