


P.C. LAYOUT



CONTACT ARRANGEMENT:

code for x	function	actuator in position 1	actuator opposite to pos. 1
D	On-On	1-2	2-3

code for x	function	actuator in position 1	actuator in center	actuator opposite to pos. 1
E	On-Off-On	1-2	open	2-3

RATING AND CONTACT/TERMINAL MATERIAL:

y	contacts	terminals	rating
empty	silver plated, copper alloy	silver plated, copper alloy	28 VDC / 3 A 120 VAC / 3 A 250 VAC / 1 A * see remark
B	gold plated over nickel	gold plated over nickel	0.4 VA, 20 V AC/DC

Specifications:

Contact resistance: 50mOhm max.
 Insulation resistance: 1 000MOhm min.
 Dielectric strength: 1 000V RMS
 Operating temperature: -40°C to +85°C
 Mechanical life: 20 000 make-and-break cycles
 Soldering conditions: auto-soldering: 260 +/-5°C, max. 10sec.
 Material: Case: nylon, white
 Actuator / housing: nylon, black
 *Remark: Breaking capacity: 1A, 250V AC wit resistive load
 Min. load: 100mA, 10V DC

Compliance: RohS II (2011/65/EU)

Tolerances:		Date	Name	<h1>MSS 3111 xy-R</h1>
		03/06	dr	
Rename	09/15	dr	<h2>knitter-switch</h2>	<h1>30 08 25</h1>
Dimensions	11/08	dr		
Specifications	05/08	dr		
Modifications	Date	Name		Page 1/1