

Miniature Slide Switches


Specifications:

| | |
|------------------------|---|
| Contact rating: | 30 V DC, 350 mA |
| Contact resistance: | < 20 mΩ |
| Insulation resistance: | > 100 MΩ at 500 V DC |
| Dielectric strength: | 500 V, 50 Hz for the duration of 1 minute |
| Operating temperature: | – 10 °C to + 85 °C |
| Mechanical life: | minimum 10 000 operations |
| Contacts: | copper alloy, silver-plated over nickel barrier |
| Contact timing: | shorting (non-shorting only if specified) |
| Slide colour: | black, further colours on request |
| Soldering conditions: | wave-soldering – max.: 5 sec, 260 °C ± 5 °C |


6

| Models: | Operating positions | Length (mm) | |
|---------|---------------------|-------------|---|
| | | A | B |


| | | | | |
|----------|---|--|------|------|
| MFP 1220 | 2 | | 13.0 | 7.5 |
| MFP 1320 | 3 | | 15.5 | 10.0 |
| MFP 1620 | 6 | | 23.0 | 17.5 |



| | | | | |
|--------------|---|--|------|------|
| MFP 1220 – R | 2 | | 13.0 | 7.5 |
| MFP 1320 – R | 3 | | 15.5 | 10.0 |



| | | | | |
|----------|---|--|------|------|
| MFP 1323 | 3 | | 15.5 | 10.2 |
| MFP 1424 | 4 | | 18.0 | 12.5 |



| | | | | |
|--------------|---|--|------|------|
| MFP 1323 – R | 3 | | 15.5 | 10.1 |
|--------------|---|--|------|------|

