


slider shown in pos. 1

**CONTACT ARRANGEMENT**

code for x	function	actuator in position 1	actuator opposite to pos. 1
D	On-On	1-2, 4-5	2-3, 5-6

code for x	function	actuator in position 1	actuator in center	actuator opposite to pos. 1
E	On-Off-On	1-2, 4-5	open	2-3, 5-6

**P.C. MOUNTING**



**Specifications:**

- Contact rating:** max. 0.4VA, max. 48V AC or DC, max. 50mA  
min.: 1µA, 20mV AC or DC
- Contact resistance:** 50mOhm max.
- Insulation resistance:** 500MOhm min. at 250V DC
- Dielectric strength:** 500V, 50Hz for the duration of 1 minute
- Operating temperature:** -20°C to +80°C
- Electrical life:** min. 40 000 cycles
- Soldering conditions:** wave-soldering: 260 +/-5°C, 5 +/-1sec.
- IP rating:** IP67
- Material:** Actuator: PBT, yellow  
Housing: brass, nickel plated  
Case: PA 66 (UL94V-0)  
Switch support: brass, tin plated  
Contact / terminals: phosphor bronze, gold plated over nickel barrier  
Cap: silicone rubber

**Compliance: RohS III (2015/863/EU)**

Tolerances: 0.00: ±0.25mm 0.0: ±0.40mm	Date	Name	<h1>ASE 2x RA</h1>
	07/13	dr	
Material	06/20	dr	<h2>30 28 91</h2>
Modifications	Date	Name	
<b>knitter-switch</b>			Page 1/1