


P.C. MOUNTING



**CONTACT ARRANGEMENT**

code for x	function	toggle in pos. a	toggle in pos. c
D	On-On	2-3	1-2
F	On-Mom	2-3	1-2

code for x	function	toggle in pos. a	toggle in pos. b	toggle in pos. c
E	On-Off-On	2-3	open	1-2
G	Mom-Off-Mom			
H	On-Off-Mom			

**Specifications:**

- Contact rating:** max.: 0.4VA, 48V AC or DC, 50mA  
min.: 1µA, 20mV AC or DC
- Contact resistance:** 50mOhm max.
- Insulation resistance:** 1000MOhm min.
- Dielectric strength:** 500V RMS
- Operating temperature:** -20°C to +85°C
- Electrical life:** 40 000 make-and-break cycles
- Soldering conditions:** wave-soldering: 260 +/-5°C, 5 +/-1sec.
- Protection:** IP67
- Material:** Actuator: brass, chrome plated  
Bushing / housing: steel  
Case: glass filled PBT (UL94V-0)  
Switch support: brass, tin plated  
Contact / terminals: phosphor bronze, gold plated over nickel barrier



Tolerances: 0.00: ±0.25mm 0.0: ±0.40mm	Date	Name
	02/14	dr

**ATE 1 x-VM**

**knitter-switch**

**30 30 44**

Page

1/1

Modifications	Date	Name
---------------	------	------