



toggle shown in pos. a



P.C. MOUNTING



CONTACT ARRANGEMENT

code for x	function	toggle in pos. a	toggle in pos. c
D	On-On	2-3, 5-6	1-2, 4-5
F	On-Mom	2-3, 5-6	1-2, 4-5

code for x	function	toggle in pos. a	toggle in pos. b	toggle in pos. c
E	On-Off-On	2-3, 5-6	open	1-2, 4-5
G	Mom-Off-Mom			
H	On-Off-Mom			

Specifications:

- Contact rating: max.: 0.4VA, 48V AC or DC, 50mA
min.: 1µA, 20mV AC or DC
- Contact resistance: 50mOhm max. at 2-4V DC, 100mA
- Insulation resistance: 1000MOhm min.
- Dielectric strength: 500V RMS
- Operating temperature: -20°C to +85°C
- Electrical life: 40 000 make-and-break cycles
- Soldering conditions: wave-soldering: 260 +/-5°C, 5 +/-1sec.
- Protection: IP67
- Material: Actuator: brass, chrome plated
Bushing / housing: steel
Case: glass filled PBT (UL94V-0)
Contact / terminals: phosphor bronze, gold plated over nickel barrier



Tolerances: 0.00: ±0.25mm 0.0: ±0.40mm		Date	Name	<h1>ATE 2 x</h1>
		03/14	dr	
			<h2>knitter-switch</h2>	<h1>30 30 53</h1>
Modifications				1/1
Date	Name			