


Toggle shown in pos. 1

P.C. MOUNTING



CONTACT ARRANGEMENT:

code for x	function	toggle in position 1	toggle opposite to pos. 1
D	On-On	2-3	1-2
F	On-Mom		

code for x	function	toggle in position 1	toggle in center	toggle opposite
E	On-Off-On	2-3	open	1-2
G	Mom-Off-Mom			
H	On-Off-Mom			

Specifications:

Contact resistance: 20mOhm max. at 2-4V DC
 Insulation resistance: 1 000MOhm min.
 Dielectric strength: 1 000V RMS
 Operating temperature: -30°C to +85°C
 Mechanical life: 30 000 make-and-break cycles
 Material: Case / bushing: PA66, UL94V-0
 Actuator: brass, chrome plated
 IP rating: IP67



Tolerances:	Date	Name
0.00: ±0.25mm	06/07	dr
0.0: ±0.40mm		

TST 1 x y

Revised	01/14	dr	knitter-switch	30 11 41	Page
IP rating	04/12	dr			1/2
Revised	10/09	dr			
Modifications	Date	Name			

RATING AND CONTACT/TERMINAL SURFACE

y	contacts	terminals	rating
Q	Ag over Ni	Ag over Ni	28 VDC / 3 A 125 VAC / 3 A 250 VAC / 1 A
empty	Au over Ni	Au over Ni	0.4 VA, max. 20 V AC/DC
G	Au over Ag over Ni	Au over Ag over Ni	28 VDC / 3 A 125 VAC / 3 A 250 VAC / 1 A
T	Au over Ag over Ni	Sn	28 VDC / 3 A 125 VAC / 3 A 250 VAC / 1 A
X	Au over Ni	Sn	0.4 VA, max. 20 V AC/DC



Tolerances: 0.00: ±0.25mm 0.0: ±0.40mm		Date	Name	TST 1 x y
		06/07	dr	
			knitter-switch	30 11 41
Modifications			Date	Name
				Page 2/2